

PATENT  
Atty. Dkt. No. WEAT/0499

**IN THE CLAIMS:**

Please amend the claims as follows:

1. (Original) A sand screen for use in a wellbore, comprising:  
a length of tubular having perforations therethrough; and  
a filtering member disposed around an outer wall of the tubular and covering at least some of the perforations, the filtering member comprising a wire wound around the outer wall to form a substantially seamless tubular shape.
2. (Original) The sand screen of claim 1, wherein the wire has offset overlapping portions.
3. (Original) The sand screen of claim 1, wherein overlapping portions of the wire are substantially non-offset.
4. (Original) The sand screen of claim 1, wherein the filtering member further comprises a mandrel that the wire is wound around.
5. (Original) The sand screen of claim 1, wherein the filtering member further comprises a mandrel that the wire is wound around, the mandrel having end rings separated by longitudinal members.
6. (Original) The sand screen of claim 1, wherein the wire is a multifilament wire.
7. (Original) The sand screen of claim 1, further comprising a seal at each end of the filtering member.
8. (Original) The sand screen of claim 1, wherein the filtering member is sintered.

Page 2

387646\_2

9. (Original) The sand screen of claim 1, wherein the filtering member further comprises sized particles packed in an annular area between the substantially seamless tubular shape and a second tubular member having apertures therethrough.
10. (Original) The sand screen of claim 9, wherein the second tubular member is wound wire.
11. (Withdrawn) A method for filtering fluids in a wellbore using a sand screen, comprising:  
disposing a filtering member around the outer wall of a tubular having one or more perforations, the filtering member being constructed by:  
rotating a mandrel;  
winding a wire around the mandrel into a tubular shape having a wall defined by overlapping sections of the wire; and  
placing the tubular into the wellbore.
12. (Withdrawn) The method of claim 11, wherein the mandrel is a perforated tubular.
13. (Withdrawn) The method of claim 11, further comprising removing the mandrel from the tubular shape.
14. (Withdrawn) The method of claim 11, further comprising positioning the mandrel around an outer wall of a tubular having perforations therethrough, thereby covering at least some of the perforations.
15. (Withdrawn) The method of claim 11, wherein the winding the wire offsets overlapping portions of the wire.
16. (Withdrawn) A method for using a sand screen, comprising:

placing the sand screen proximate a substance to be filtered, wherein the sand screen is produced by:

winding a wire into a substantially seamless tubular shape to provide a filtering member;

positioning the filtering member around an outer wall of a tubular having perforations therethrough thereby covering at least some of the perforations; and

circumferentially sealing the filtering member to the tubular at each end of the filtering member.

17. (Withdrawn) The method of claim 16, further comprising sintering the filtering member thereby diffusion bonding contact points of the wire.

18. (Withdrawn) The sand screen of claim 16, wherein the winding the wire offsets overlapping portions of the wire.

19. (Withdrawn) A method for filtering fluids in a wellbore using a sand screen, comprising:

lowering the sand screen into the wellbore, wherein the sand screen is configured by:

winding a wire to form a coil in a substantially seamless tubular shape;

positioning the coil relative to a first tubular having a different diameter

than the coil to provide an annular area between the coil and the first tubular;

packing the annular area with sized particles to provide a packing;

sealing ends of the annular area thereby retaining the packing to provide a filtering member;

positioning the filtering member around an outer wall of a second tubular

having perforations therethrough thereby covering at least some of the perforations; and

circumferentially sealing the filtering member to the tubular at each end of

the filtering member; and  
filtering well fluids.

20. (Withdrawn) The method of claim 19, wherein the first tubular is wound wire.

21. (Withdrawn) The method of claim 19, wherein the first tubular is selected from the group consisting of slotted tubing, wire wrapped screen, wire mesh, and premium screen.

Please add the following new claims:

22. A method filtering fluids in a wellbore using a sand screen comprising:  
providing a tubular with a filtering member wherein the filtering member comprises a wire wound around the outer wall to form a substantially seamless tubular shape;  
placing the filtering member into the wellbore;  
flowing fluids past the filtering member and into the tubular through perforations in the tubular;  
filtering the fluids with the filtering member as the fluid passes the filtering member.